

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

- 1.1 PRODUCT IDENTIFIER:** Bona Craft Oil 2K Component A
- 1.2 PRODUCT CODE:** Not applicable.
- 1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:**
- RELEVANT IDENTIFIED USES:** Oil for the treatment of wooden floors and other wooden surfaces.
RESTRICTIONS ON USE: For professional use only.
- 1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**
- SUPPLIER NAME:** Bona Australia Pty Ltd (ABN: 2208 758 1520),
ADDRESS: Unit 9, Wareca Business Park
1866 Princes Highway, Clayton, Victoria, 3168
E-MAIL: info@bona.com.au
TELEPHONE NUMBER: 03 9543 4399
- 1.5 EMERGENCY TEL. NUMBER:** 03 9543 4399 Business Hours. (0408 008 762 After Hours or National Chemical Emergency Centre Europe 18000 74234.)

SECTION 2 – HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD CLASS & CATEGORY:

Under the Model Work Health and Safety Regulations, the product would not be classified as hazardous.

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Not Applicable.
PICTOGRAMS: Not Applicable.
HAZARD STATEMENTS: Not Applicable.

PRECAUTIONARY STATEMENTS:

PREVENTION: Not Applicable.
RESPONSE: Not Applicable.
STORAGE: Not Applicable.
DISPOSAL: Not Applicable.

2.3 OTHER HAZARDS:

The mixture has a low order of toxicity associated with it. May cause mild gastric irritation if swallowed. Excessive exposure may result in mild irritation to the skin or respiratory system as well as possible irritation to the eye. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

Contains drying oils. Cloths, rags, paper and similar materials contaminated with oil should be placed in water or in a sealed metal container to minimise the potential of the risk of self-ignition.

SAFETY DATA SHEET

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Naphtha, petroleum, hydrotreated heavy	64742-48-9	≤ 3%	Asp Haz 1 - H304
Other non-hazardous ingredients	-	To 100%	Not Applicable

* Please see Section 15 of this SDS for the full text description of the Label Elements.

SECTION 4 – FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION: Rinse mouth out with water. If swallowed, according to the manufacturer, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. If irritation develops or persists or vomiting has occurred after ingestion, seek medical assistance.

EYE: If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.

SKIN CONTACT: If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. Do NOT use solvents and/or thinners. If irritation develops or persists, consult a doctor.

INHALATION: If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops/persists, consult a doctor.

PROTECTION FOR FIRST AIDERS:

No personnel shall place themselves in a situation that is potentially hazardous to themselves. As a precaution, assess the scenario for PPE requirements before entering by assessing the environment for vapours. Do not enter contaminated area without a respirator. As the product is a wood treatment, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

FIRST AID FACILITIES: Eye wash fountain and safety showers are recommended in the area where the product is used. As a minimum, a source of running, potable water must be available.

4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

ACUTE: Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Ingestion may lead to nausea. Eye contact may lead to localised burning, redness and tearing. Skin contact may lead to redness or itching.

SAFETY DATA SHEET

SECTION 4 – FIRST AID MEASURES - Continued

CHRONIC: Repeated or prolonged contact with the preparation may cause removal of the natural fats and oils from the skin. Repeated or prolonged skin contact may also aggravate/exacerbate existing skin conditions, such as dermatitis.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:

ADVICE TO DOCTOR: Treat symptomatically. The manufacturer recommends that if large quantities have been ingested or inhaled a Poisons Specialists should be contacted immediately as a precaution.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA: Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, alcohol resistant foam, dry chemical or water fog. Spray down fumes resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning. Water may cause splattering on hot residues.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon and nitrogen as well as smoke and irritating vapours.

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: This product is not flammable under conditions of use. It is a coating product that will burn if preheated. Keep storage areas and fire exposed surfaces, etc, cool with water spray. Do not allow runoff from a fire to enter drains, sewers or waterways.

HAZCHEM CODE: Not applicable.

EXPLOSION: No information to indicate that the product is an explosion hazard. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

PROTECTIVE EQUIPMENT:

In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION: For spills, wear Nitrile Rubber gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant bodysuit is recommended, and the atmosphere must be evaluated for oxygen deficiency. If in doubt wear self-contained breathing apparatus.

SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES - Continued

CONTROL MEASURES: Ventilate area and extinguish and/or remove all sources of ignition. Stop the leak if safe to do so. **CAUTION:** The spilled product will be slippery. Avoid contact with the spilled material.

EMERGENCY PROCEDURES:

In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE: Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT: Contain the spill and absorb with a proprietary absorbent material, sand or earth. **CAUTION:** The spilled product will be slippery. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

CLEANING PROCEDURES: Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Please note that the product contains drying oils. Cloths, rags, paper and similar materials contaminated with oil from cleaning processes, should be placed in water or in a sealed metal container to minimise the potential of the risk of self-ignition.

CAUTION: The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been banded, the material can be pumped into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING: Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. A full-face shield should be used if there is the potential for the product to enter the eye via processes such as mixing or splashes. Prevent small spills and leakage to avoid slip hazards. As the product is vegetable oil based, properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards or potential self-ignition of cleaning materials. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Always keep in containers made of the same material as the original one. Never use pressure to empty the container; the container is not a pressure vessel. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers.

SAFETY DATA SHEET

SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED - Continued

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

SAFE STORAGE: Store in a dry, well ventilated, frost-free area away from direct sunlight, ignition sources, oxidising agents, strong acids and alkalis, foodstuffs, animal feeds and clothing. Keep containers closed when not in use. Always keep in containers made of the same material as the original one. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect the packaging from damage. When the packaged material is intact the product is deemed to be of limited hazard.

INCOMPATIBILITIES: Avoid oxidising agents, including strong acids, and strongly alkaline materials.

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure standards for the product have not been established. There are no known exposure standards for the product as mists or vapours.

8.2 BIOLOGICAL MONITORING: No data available.

8.3 CONTROL BANDING: No data available.

8.4 ENGINEERING CONTROLS:

ENGINEERING CONTROLS: Use product in a well-ventilated area. Where reasonably practical this should be achieved by the use of local exhaust ventilation and good general extraction. Special ventilation is not normally required. However, in the operation of certain equipment, in enclosed spaces or at elevated temperatures, mists or vapours may be generated and exhaust ventilation may be required to maintain airborne concentration levels below a level considered irritating by individuals.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact. If when mixing or stirring the product there is the possibility of splashing, a full-face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of skin contact with the material; wear gloves to provide hand protection. Nitrile rubber gloves are recommended.

SKIN (CLOTHING) PROTECTION: During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to re-use.

SAFETY DATA SHEET

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION - Continued

RESPIRATORY PROTECTION: Use only in well-ventilated areas. During routine operation, a respirator is not required. Dry sanding, grinding, flame/heat stripping and cutting of the dry film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation during such operations, suitable respiratory protective equipment, such as an approved organic vapour/particulate respirator is required. If irritating mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

THERMAL PROTECTION: Not applicable.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Liquid, various colours.
ODOUR:	No data available.
ODOUR THRESHOLD:	No data available.
pH:	No data available.
MELTING/FREEZING POINT:	No data available.
INITIAL BOILING POINT:	No data available.
BOILING RANGE (°C):	No data available.
FLASHPOINT (°C):	Typically, >95° C (Closed cup).
EVAPORATION RATE:	No data available.
FLAMMABILITY LIMITS (%):	No data available.
VAPOUR PRESSURE (kPa):	No data available.
VAPOUR DENSITY:	No data available.
DENSITY (g/mL @ 20°C):	Typically, 0.95.
SOLUBILITY IN WATER(g/L):	Insoluble in water.
PARTITION COEFFICIENT:	No data available for n-octanol/water.
AUTO-IGNITION TEMP (°C):	No data available.
DECOMPOSITION TEMP (°C):	No data available.
VISCOSITY (Dynamic):	No data available.
VISCOSITY (@ 40°C):	No data available.

SECTION 10 – STABILITY AND REACTIVITY

- 10.1 REACTIVITY:** The product does not pose any further reactivity hazards other than those listed in the following sub-sections.
- 10.2 CHEMICAL STABILITY:** Stable under recommended storage and handling conditions (see section 7).
- 10.3 POSSIBILITY OF HAZARDOUS REACTIONS:**
Keep away from oxidising agents, including strong acids and strong alkalis. Hazardous polymerisation does not occur.
- 10.4 CONDITIONS TO AVOID:** Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use.
- 10.5 INCOMPATIBLE MATERIALS:** Avoid oxidising agents, strong acids and strong alkaline materials.

SAFETY DATA SHEET

SECTION 10 – STABILITY AND REACTIVITY - Continued

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and has the following test data.

Naphtha, petroleum, hydrotreated heavy

Oral - LD50 (Rat): > 5,000 mg/kg

Dermal - LD50 (Rabbit): > 3,200 mg/kg

Inhalation - LC50 (Rat, vapour, 4 hours): 8,500 mg/m³

11.2 SWALLOWED:

This product is expected to have a low order of toxicity associated with it when ingested. Ingestion may cause irritation to the mouth, throat and digestive tract. Ingestion of significant quantities may lead to irritation to the stomach and the person may feel nauseous. As the product is a wood treatment product, aspiration into the lungs may be an issue if vomiting has occurred after ingestion or if stomach irrigation is deemed necessary. If the product is ingested and the person has vomited, they should be observed to ensure there is no aspiration into the lungs. During normal usage, ingestion should not be a means of exposure.

11.3 SKIN CORROSION / IRRITATION:

This product is not expected to exhibit Dermal Corrosivity/Irritation, based on the available data and the known hazards of the components. May be mildly irritating to the skin. Prolonged or repeated contact may cause removal of the natural fat from the skin, resulting in non-allergic contact dermatitis and possibly absorption through the skin. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

11.4 SERIOUS EYE DAMAGE / IRRITATION:

This product is not expected to exhibit Eye Irritation or Serious Damage/ Corrosivity, based on the available data and the known hazards of the components according to the manufacturer. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.

11.5 RESPIRATORY OR SKIN SENSITISATION:

This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.

11.6 GERM CELL MUTAGENICITY:

This product is not expected to be mutagenic based on the available data and the known hazards of the components.

11.7 CARCINOGENICITY:

This product is not expected to be a carcinogen based on the available data and the known hazards of the components.

SAFETY DATA SHEET

SECTION 11 – TOXICOLOGICAL INFORMATION - Continued

11.8 REPRODUCTIVE TOXICITY:

This product is not expected to be a reproductive hazard based on the available data and the known hazards of the components.

11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) –

SINGLE EXPOSURE: This product is not expected to cause organ damage from a single exposure, based on the available data and the known hazards of the components. This product is not expected to pose an irritation hazard at ambient temperature or under normal handling conditions. Not classified as a respiratory irritant, however inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose, throat and respiratory system.

11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) –

REPEATED EXPOSURE: This product is not expected to cause organ damage from prolonged or repeated exposure, based on the available data and the known hazards of the components.

11.11 ASPIRATION HAZARD: This product is not expected to be an aspiration hazard, based on the available data and the known hazards of the components. As the product is a wood treatment product, aspiration into the lungs may be an issue if vomiting has occurred after ingestion or if stomach irrigation is deemed necessary. As a precaution, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects.

11.12 OTHER INFORMATION: No other information is available.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ECOTOXICITY:

There is no data available for the product as a whole.

Naphtha, petroleum, hydrotreated heavy

LC₅₀(Fish, 96 hrs): > 100 mg/L

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

12.2 PERSISTENCE & DEGRADABILITY:

No persistence or biodegradability data is available for the product. The manufacturer nominates that Naphtha (petroleum), hydrotreated heavy component is readily biodegradable.

12.3 BIOACCUMULATIVE POTENTIAL:

No information is available for the product. The manufacturer nominates that Naphtha (petroleum), hydrotreated heavy component has a BCF of 10 to 2500 and a high bioaccumulative potential.

12.4 MOBILITY IN SOIL:

No information is available for the product.

12.5 OTHER ADVERSE EFFECTS:

Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs. The product is not miscible with water. The manufacturer nominates that the mixture does not contain and PBT or vPvB components.

SAFETY DATA SHEET

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 DISPOSAL METHODS:

PRODUCT: The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. Do not pour leftover product down the drain. Small quantities of unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via normal domestic or industrial waste collection.

CONTAINERS: Empty containers may contain residual material. They should be completely drained and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. Empty containers should be recycled wherever possible rather than being sent to landfill or incinerated. If being sent to landfill any residual product must be allowed to dry/cure before disposal.

SECTION 14 – TRANSPORT INFORMATION

This product is not regulated for land, sea or air transportation.

14.1 LAND (ADG Code):

UN NUMBER:	Not applicable
UN PROPER SHIPPING NAME:	Not applicable
TRANSPORT HAZARD CLASS(ES):	Not applicable
PACKAGING GROUP:	Not applicable
ENVIRONMENTAL HAZARDS:	Not applicable
SPECIAL PRECAUTIONS FOR USER:	Not applicable
HAZCHEM CODE:	Not applicable

14.2 SEA (IMDG):

UN NUMBER:	Not applicable
UN PROPER SHIPPING NAME:	Not applicable
TRANSPORT HAZARD CLASS(ES):	Not applicable
PACKAGING GROUP:	Not applicable
ENVIRONMENTAL HAZARDS:	Not applicable
SPECIAL PRECAUTIONS FOR USER:	Not applicable

14.3 AIR (IATA):

UN NUMBER:	Not applicable
UN PROPER SHIPPING NAME:	Not applicable
TRANSPORT HAZARD CLASS(ES):	Not applicable
PACKAGING GROUP:	Not applicable
ENVIRONMENTAL HAZARDS:	Not applicable
SPECIAL PRECAUTIONS FOR USER:	Not applicable

SAFETY DATA SHEET

SECTION 16 – ANY OTHER RELEVANT INFORMATION - Continued

IMDG	International Maritime Dangerous Goods
IUCLID	International Uniform Chemical Information Database
LC ₅₀	Median Lethal Concentration
LD ₅₀	Median Lethal Dose
NICNAS	National Industrial Chemicals Notification & Assessment Scheme
NOHSC	National Occupational Health and Safety Commission
OECD	Organisation for Economic Co-Operation and Development
OSHA	Occupational Safety and Health Administration
PBT	Persistent, Bioaccumulative and Toxic
PPE	Personal Protective Equipment.
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RTECS	Registry of Toxic Effects of Chemical Substances
STEL	Short Term Exposure Limit
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
TWA	Time-Weighted Average
UN Number	United Nations Number
vPvP	Very Persistent and Very Bioaccumulative
WHS	Work Health and Safety
%W/W	Percent Weight for Weight

LITERATURE REFERENCES AND SOURCES OF DATA:

Annex I: OECD Test Guidelines for Studies Included in SIDS
Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]
Assigning a Hazardous Substance to a Group Standard
Australian Dangerous Goods Code 7th Edition
Correlation between GHS and New Zealand HSNO Hazard Classes and Categories
Guidance on the Classification of Hazardous Chemicals under the WHS Regulations
Hazardous Substance Information System (HSIS) - Guidance Material for Hazard Classifications
HSNO Control Regulations
International Toxicity Testing Guidelines
Labelling of Hazardous Substances Hazard and Precautionary Information
Manual for the Assessment of Chemicals Chapter 2 Data Gathering
Model Work Health and Safety Regulations - Transitional Principles
Model Work Health and Safety Regulations.
NICNAS IMAP Human Health Tier II Assessment for Hydrocarbon Solvents Commonly Used in Their Refined Forms including CAS Number: 64742-48-9
OECD Guidelines for Testing of Chemicals
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
Record of Group Standard Assignment
Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances
Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996
User Guide to the HSNO Thresholds and Classification
Workplace Exposure Standards and Biological Exposure Indices
Workplace Exposure Standards for Airborne Contaminants

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. The information presented here within, is based upon the product information supplied by the manufacturer. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.